

2024 Wheel Days

BONESTOCK COMPACTS

1. You may move the battery inside, safely secured! 1 battery only.
2. The gas tank may be relocated inside or left in stock position if in front of rear axel, fuel cells may be used. If using original or boat tank they must be covered. Fuel cell not required to be covered.
3. A 4-point simple cage may be used, it may not extend more than 3" past the door post. 6x6x1/4 max material size.
4. Bumpers- must remain stock! No swaps allowed, all bumpers must be held on with 2 or 3 strands of 9 wire or a small chain.
5. Hoods/Trunks- may be bolted, chained or 9 wired. If bolted, you are allowed 4 bolts in each 3/8" max. Chains may not exceed 3/8" 4 spots each. 2 strands of 9 wire in 4 locations only. (Rear bumper to roof or anywhere in between) Approximately a 12"x12" hole cut in the hood is recommended. Also hood to roof chains or bars is suggested.
6. Welding- You may weld the driver's door solid and the passenger door 4" on 4" off 4x4x1/4" maximum material. Cages allowed to be welded in. No other welding allowed!!!
7. Simplified harness may be used.
8. Rear tire pan may be jacked up (no other body modifications will be allowed)
9. Tire tube's will be allowed (nothing else done to the tires is allowed, stock DOT tires only)
10. If it's not in the rules don't do it, this is stock class. All judges' decisions are final.
11. Class is open to any FWD car 4 or 6 cylinder, if rear drive they must be under 107".

No AWD allowed